



Pura Flow

500 Reverse Osmosis System

Experience the Difference

Five Stage System with Single Cartridge Design

The ultra-compact **PuraFlow Reverse Osmosis System** utilizes reverse osmosis technology and features a four stage prefilter, membrane, and postfilter design which is housed inside a single cartridge. A fifth stage post-polishing inline carbon filter is installed between the tank and faucet for even better tasting water.

The system includes a non-metallic faucet, a two gallon white storage tank, tubing, and quick connect fittings for a fast and easy installation.

- Stage 1** 20 Micron Sediment Prefilter
- Stage 2** GAC Prefilter
- Stage 3** 50 GPD (189.3 LPD) Thin Film Composite Reverse Osmosis Membrane
- Stage 4** Post Carbon Filter
- Stage 5** In-line GAC Postfilter

*5-stage PuraFlow 500 Reverse Osmosis System
Compared to a Typical 5-Stage Component System*

PF-02-1001

**Actual product may vary*



More Water to the Tank, Less Water to the Drain

This single cartridge designed system takes advantage of cutting edge high flow membrane technology. In addition, a unique flow path gives the **PuraFlow Reverse Osmosis System** a superior waste-to-product ratio. The combination of the two means more water to the tank and less water to the drain. The high flow membrane also ensures faster tank refilling.

Compact and Lightweight

The **PuraFlow Reverse Osmosis System** has been designed to take up less space under the sink. The complete system including the tank is approximately the same height and width of a standard system's tank. The entire system is less than 14 inches in depth and can be lifted easily with one hand. The small footprint of this system makes it easier to install in cramped kitchen or bathroom cabinets.

PuraFlow 500 Reverse Osmosis System



Pure Water ... Experience the Difference

Saves Time and Money

With only one main cartridge and one inline carbon filter, the **PuraFlow Reverse Osmosis System** saves time when servicing and money on service calls and replacement cartridges.



Feed Water Requirements	
Pressure	40-80 psi (275 kPa – 552 kPa)
Temp	40°F – 100°F (4°C – 38°C)
TDS	<2000 mg/L
Turbidity	<1 NTU
SDI	<5
pH	4 – 8
Chlorine	<1.0 mg/L

Feed water must be potable, municipal water. Must be free of potential membrane foulants such as Iron, Hydrogen Sulfide and Manganese.

Performance Specifications	
	Membrane
Production	50 GPD (189.3 LPD)
NaCl Rejection	95%
Waste to Product	1.67:1

Tested at 60 psig (4 bar), 500ppm TDS municipal water, 77°F (25°C).

Dimensions and Shipping Weight			
Width	Height	Diameter	Weight
9.72" W (24.7 cm)	15.38" H (39.1 cm)	13.75" D (34.9 cm)	11 lbs. (5 kg.)

Exploded View
PF-02-1001

Pre-Plumbed

No preliminary tank or unit assembly is required. The tank, faucet, feed and drain lines are pre-plumbed in the unit and tested at the factory. Final onsite installation is faster and simpler.

Fast Flow

The **PuraFlow Reverse Osmosis System** incorporates 3/8" tubing for faucet and tank connections. This larger diameter tubing ensures a faster flow rate from the faucet.



PuraFlow

Toll-Free Phone: 888.895.2575

Email: sales@puraflow.com • Website: www.puraflow.com

Fax: 877.320.4078 • 31805 Temecula Parkway, #175 • Temecula, CA 92592

